

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A method for providing Quality of Service (QoS) routing of a network packet, the method comprising inserting a QoS code into an Internet Protocol (IP) address of the network packet, wherein the QoS code becomes part of the IP address and is defined in unused portions of the IP address.
2. (Currently Amended) The method in accordance with claim 1 further comprising:
checking unused bits of the IP address to read the QoS code upon receiving the network packet at an intermediate node on a network; and
forwarding ~~re-transmitting~~ the received network packet from the intermediate node with the QoS indicated by the QoS code.
3. (Original) The method in accordance with claim 2 further comprising storing the QoS code in the intermediate node.
4. (Original) The method in accordance with claim 1 wherein the IP address comprises an IP version 6 address.
5. (Currently Amended) A method for providing quality of service (QoS) routing of a network packet, the method comprising:
checking unused bits of an Internet Protocol (IP) address associated with the network packet to read a QoS code therein upon receiving the network packet at an intermediate node on a network, and wherein the QoS code is part of the IP address and included within the unused bits of the IP address; and
forwarding ~~re-transmitting~~ the received network packet from the intermediate node with the QoS indicated by the QoS code.
6. (Original) The method in accordance with claim 5 further comprising storing the QoS code in the intermediate node.

7. (Original) The method in accordance with claim 6 wherein the IP address comprises an IP version 6 address.

8. (Currently Amended) A method for providing quality of service (QoS) routing of a network packet, the method comprising:

associating one of a plurality of QoS codes with one [[each]] of a plurality of QoS levels;
inserting one of the QoS codes into unused bits of an IPv6 address of the network packet,
wherein the QoS codes are part of the IPv6 address and included in unused bits of the IPv6 address ;

checking the unused bits of the IPv6 address to read the QoS code therein upon receiving the network packet at an intermediate node on a network; and

forwarding ~~re-transmitting~~ the received network packet from the intermediate node with the QoS indicated by the QoS code.

9. (Original) The method in accordance with claim 8 further comprising the step of storing the QoS code in the intermediate node.

10. (Currently Amended) Apparatus for providing Quality of Service (QoS) routing of a network packet, the apparatus comprising means for inserting a QoS code into an Internet Protocol (IP) address of the network packet, wherein the QoS code is part of the IP address and is included in unused portions of that IP address.

11. (Original) The apparatus in accordance with claim 10 further comprising:

means for checking unused bits of the IP address to read the QoS code upon receiving the network packet at an intermediate node on a network; and

means for forwarding ~~re-transmitting~~ the received network packet from the intermediate node with the QoS indicated by the QoS code.

12. (Original) The apparatus in accordance with claim 11 further comprising means for storing the QoS code in the intermediate node.
13. (Currently Amended) Apparatus for providing quality of service (QoS) routing of a network packet, the apparatus comprising:
- means for checking unused bits of an Internet Protocol (IP) address associated with the network packet to read a QoS code therein upon receiving the network packet at an intermediate node on a network, wherein the QoS code is part of the IP address and included within the unused bits; and
 - means for forwarding ~~re-transmitting~~ the received network packet from the intermediate node with the QoS indicated by the QoS code.
14. (Currently Amended) The apparatus method ~~method~~ in accordance with claim 13 further comprising means for storing the QoS code in the intermediate node.
15. (Currently Amended) The apparatus method ~~method~~ in accordance with claim 14 wherein the IP address comprises an IP version 6 address.
16. (Currently Amended) The computer readable medium containing executable instructions for providing Quality of Service (QoS) routing of a network packet through a network, the executable program instructions comprising program instructions for inserting a QoS code into an Internet Protocol (IP) address of the network packet, wherein the QoS code becomes part of the IP address and is included in unused bits of the IP address.
17. (Original) The computer readable medium in accordance with claim 16, wherein the executable program instructions further comprise program instructions for associating one of a plurality of QoS codes with one ~~one~~ ~~of~~ ~~each~~ of a plurality of QoS levels.

18. (Currently Amended) The computer readable medium in accordance with claim 16, wherein the executable program instructions further comprise program instructions for:

checking unused bits of the IP address to read the QoS code upon receiving the network packet at an intermediate node on a network; and

forwarding ~~re-transmitting~~ the received network packet from the intermediate node with the QoS indicated by the QoS code.

19. (Original) The computer readable medium in accordance with claim 18, wherein the executable program instructions further comprises program instructions for storing the QoS code in the intermediate node.

20. (Original) The computer readable medium in accordance with claim 19, wherein the IP address comprises an IP version 6 address.

21. (Currently Amended) A computer readable medium containing executable instructions for providing Quality of Service (QoS) routing of a network packet through a network, the executable program instructions comprising program instructions for:

checking unused bits of an Internet Protocol (IP) address associated with the network packet to read a QoS code therein upon receiving the network packet at an intermediate node on a network, wherein the QoS code is part of the IP address and included in the unused bits; and

forwarding ~~re-transmitting~~ the received network packet from the intermediate node with the QoS indicated by the QoS code.

22. (Original) The computer readable medium in accordance with claim 21, wherein the executable program instructions further comprise program instructions for associating one of a plurality of QoS codes with one [[each]] of a plurality of QoS levels.

23. (Currently Amended) A method for providing Quality of Service (QoS) routing of a network packet through intermediate nodes on a network, said method comprising the steps of:
- checking unused bits of an Internet Protocol (IP) address associated with the network packet to read a QoS code therein upon receiving the network packet at an intermediate node on a network, wherein the QoS code is part of the IP address and is included in the unused bits of the IP address;
 - storing the network packets in queues based upon the QoS indicated by the QoS code;
 - reading said network packets from said queues in a preferential manner; and
 - forwarding ~~re-transmitting~~ the stored network packets read from the queues with the QoS indicated by the QoS code.
24. (Original) The method in accordance with claim 23 further comprising the steps of:
- associating one of a plurality of QoS codes with one [[each]] of a plurality of QoS levels;
 - storing the plurality of QoS codes in the intermediate node; and
 - determining the QoS level that a network packet should be retransmitted with by using the QoS code read from the network packet during the step of checking unused bits to identify the associated QoS level.
25. (Original) The method in accordance with claim 24 wherein the IP address is an IP version 6 address.